



## ARIES CABLE

### FEATURES

- A cable-based telemetry system is only as good as the cables. ARIES cables are designed and manufactured to the highest specifications to ensure maximum reliability.
- ARIES cables boast the highest Strength-to-Weight ratio in the industry. ARIES II is over 50Kg tensile strength per Kg weight (per 100m). That's lighter and more than twice as strong, per Kg of cable weight, as any competitor's cable on the market.

### SPECIFICATIONS

#### Land-Lt (ARIES I)

Weight: 4.77Kg/100m  
 Tensile: 156Kg, typical  
 Jacket: Single, water blocked heads & takeouts

#### Land-Com (ARIES I)

Weight: 6.35Kg/100m  
 Tensile: 288Kg, typical  
 Jacket: Double, water blocked heads & takeouts

#### Land-II

Weight: 6.59Kg/100m  
 Tensile: 360Kg, typical  
 Jacket: Double, water blocked heads & takeouts

#### Transverse

Weight: 8.3Kg/100m  
 Tensile: 340Kg, typical  
 Jacket: Double, water blocked heads

#### Marine Medium Duty

Weight: 13.4Kg/100m  
 Tensile: 344Kg, typical  
 Jacket: Double, fully water blocked

#### Marine Heavy Duty


Weight: 17.15Kg/100m  
 Tensile: 727Kg, typical  
 Jacket: Double, fully water blocked

### PHYSICAL


Operating temperature: -45°C to +70°C



### TAKEOUT CONNECTORS



KCM-Male



KCM-Female



LCK-Male



LCK-Female

Other connectors are available upon request